

IN STOCK

HWM

LiSEC, Horizontal Washing Machines



HWM

Technical Specifications:

Glass Sizing & Load Capacities

Glass Width Options: 1.3 m / 2.3 m / 2.6 m / 2.8 m / 3.3 m
Glass Thickness Range: 2 – 35 mm
Minimum Glass Size (Standard): 400 × 200 mm
Minimum Glass Size (HWM13B): * 210 × 210 mm
Conveyor Height: 950 mm (adjustable by ±30 mm)
Maximum Weight Load: 88 kg/m²

Performance & Mechanical Configuration

Maximum Processing Speed (3 mm glass): 12 m/min
Cylindrical Brushes: Available setups with 4, 6, or 8 brushes
Heated Water Tanks: 2 (1) / 3 (1) / 4 (2)
Tank reading guide: The number in brackets shows how many tanks are heated out of the total count. For example, "4 (2)" means there are 4 tanks in total, and 2 of them are heated.

Water consumption values apply only when the water treatment system is active.

<i>Model</i>	<i>Dimensions L×W×H (mm)</i>	<i>Electrical Cons.</i>	<i>Air Pressure</i>	<i>Air Cons.</i>	<i>Water Cons.*</i>
HWM13B*	5,300 × 4,700 × 4,900	45 kVA	7 bar	60 L/min	2 L/min
HWM23B*	5,300 × 5,700 × 4,900	50 kVA	7 bar	60 L/min	2–3 L/min
HWM26B*	5,300 × 6,000 × 4,900	55 kVA	7 bar	60 L/min	2–3 L/min
HWM28B*	5,300 × 6,200 × 4,900	55 kVA	7 bar	60 L/min	2–3 L/min
HWM33B*	5,300 × 6,700 × 4,900	70 kVA	7 bar	60 L/min	2–3 L/min

Fully automatic stainless-steel glass washing and drying machine with PLC control, heated water tanks, filtration system, and recirculation pumps. Equipped with motorized inlet and outlet conveyors, high-pressure pre-wash and drying sections, and up to four pairs of cylindrical brushes. Suitable for glass thicknesses from 2 to 35 mm, including Low-E and coated glass with optional soft-bristle brushes.